MATERIAL SAFETY DATA SHEET POLYSHIELD REGULAR GRAFFITI PREVENTER

SECTION I - PRODUCT IDENTIFICATION

Manufacturer's Name: American Building Restoration Products, Inc.

9720 S. 60th Street Franklin, WI. 53132

Emergency Phone No.: Chemtrec 1-800-424-9300

Product Trade Name: PolyShield Regular Graffiti Preventer

DOT Proper Shipping Name: Sealer

SECTION II - HAZARDOUS INGREDIENTS

	CAS NO.	AMT (る)	ACGIH TLV
Nonylphenol Ethoxylated	9016-45-9	2.0	
Tributoxyethyl Phosphate	78-51-3	1.83	
Diethylene Glycol Monoethyl Ether	111-90-0	1.8	
Zinc Ammonium Carbonate Compound	38714-47-5	0.76	

SECTION III - PHYSICAL DATA

Boiling Point: 212°F Specific Gravity (H2O=1): Approx 1

Vapor Pressure (mm Hg): 17.5 mm @ 25°C

Percent Volatile By Volume: 82%

Vapor Density (Air=1) Approx 1.0
Evaporation Rate (water =1): Approx 1.0
Solubility in water: Dispersible
Reactivity in Water: Non-reactive

Appearance and Odor: Light tan emulsion - mild odor.

SECTION IV - FIRE AND EXPLOSION HAZARD

Flash Point: None Flammable Limits in Air (% by volume): N/A Extinguishing Media: N/AAuto Ignition Temperature: N/A Special Fire Fighting Procedures: None Unusual Fire and Explosion Hazards: None Stability: Stable Incompatibility (Material to Avoid): None Known Hazardous Decomposition Products: None Known

MATERIAL SAFETY DATA SHEET POLYSHIELD REGULAR GRAFFITI PREVENTER

Hazardous Polymerization:

Will Not Occur

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: See Section II

Signs and Symptoms of Exposure: None Known

Chronic Over Exposure: None Known EMERGENCY AND FIRST AID PROCEDURES:

Eyes: In case of contact with eyes, flush with water for at least 15

minutes. If irritation develops, consult a physician.

Skin: Wash affected area with a mild soap and plenty of water. If irritation develops, consult a physician.

Internal: Call a Poison Control Center, Hospital Emergency Room or Physician. Unless advised otherwise, induce vomiting by giving either Syrup of Ipecac followed by 2 glasses of water or by touching the back of throat with fingers.

SECTION VI - SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled: Mop up small spills to prevent slipping. Absorb large spills with a suitable absorbent such as soil, sand or commercial absorbent.

WASTE DISPOSAL METHOD: Contact local municipal, state, or federal agencies to ensure compliance of disposal method with current regulations.

NOTE: Empty containers can have residues, gases or mists and are subject to proper waste disposal.

SECTION VII - SPECIAL PROTECTION INFORMATION

Respiratory Protection: Not Required

Ventilation: Normal Local Exhaust: None

Mechanical (General): None

Protective Gloves: Impervious gloves recommended

Eye Protection: Chemical splash goggles

Other Protective Clothing or Equipment: None

SECTION VIII - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: Keep from freezing

MATERIAL SAFETY DATA SHEET POLYSHIELD REGULAR GRAFFITI PREVENTER

SECTION IX - PREPARATION DATE OF MSDS

Occupational Health & Safety Dept.

Supersedes: 6/10/98

Date: 8/30/01

DISCLAIMER

The information contained herein is based on the data available to us and is believed to be correct. However, American Building Restoration Products, Inc. makes no warranty, expressed or implied regarding the accuracy of the results to be obtained from the use thereof. American Building Restoration Products, Inc. assumes no responsibility for injury from the use of the product described herein.

PLYPREVT